



# MT2010K

## 10" fully rugged tablet



## Compact and fully rugged, with integrated keyboard

The MT2010K™ is a fully rugged tablet that combines a compact form factor with the convenience of an integrated QWERTY keyboard and 10 programmable function buttons. The optimal choice for mobile applications where a full keyboard is required.

The 8" touchscreen is easy to read, even in sunlight, making data input fast and simple for operators in the field, both outdoors and indoors.

Tired of dealing with the repair costs of consumer-grade tablets? This tablet can withstand a four-foot drop onto concrete. It is dustproof and waterproof to IP65 standard and has an operating temperature range of -20 to +50°C / -4 to +122°F.

For a highly flexible mobile solution, this device can be easily carried for audits, special orders or inventory tasks.

### KEY FEATURES

- Windows operating system
- 8" display with optical bonding for sunlight viewability
- Intel® Celeron® N2930 processor
- Fully rugged construction, IP65 waterproof and dustproof
- Hot-swappable battery
- Withstands a four-foot drop onto concrete
- Optional integrated 1D/2D barcode reader
- Integrated QWERTY keyboard

### HIGHLIGHTS



#### Extended functionality

Get more out of your device with the right accessories



#### Perfect for work outside of the vehicle

The slim and compact format makes this fully rugged tablet the perfect choice for remote work



#### Integrated QWERTY keyboard makes data entry easier

Typing is fast and easy with the integrated QWERTY keyboard



# MT2010K 10" fully rugged tablet

## BASE UNIT

---

### Processor

Intel® Celeron® N2930

### Memory

8GB SODIMM DDR3L-1600

### Display

8" (1280 x 800) 500 NIT

Capacitive multi-touch touch screen with optical bonding for sunlight viewability

## STORAGE

---

### Onboard

SSD 64GB, 128GB, 256GB

## RF OPTIONS

---

### Radio

WLAN 802.11 a/b/g/n/ac

Bluetooth v 4.1

4G (LTE) up to 100 Mbps download speed (optional)

### GPS

GPS, Galileo

## INTERFACES

---

### Ports

1x USB 3.0

1x Micro HDMI

1x Micro SD slot

1x 30-pin combo conn. (Giga-LAN or RS232)

1x Line out/mic in

1x Power jack

### Audio

2x Stereo speaker

### Camera

5.0 MP auto focus w. LED flash (at rear)

### Data Capture

1D/2D barcode reader (optional)

### Keys

1x Power

10x Programmable function keys

Integrated QWERTY keypad (ISO/IEC 9995-3)

### LED indicators

Power

Battery

HDD

RF

## SECURITY

---

### TPM

V 2.0

### Lock

Kensington lock slot

### Mobile Device Management

SOTI Mobicontrol compatible, available upon request

## SENSORS

---

Digital compass

Light sensor

G-sensor

## POWER SUPPLY

---

### Input

19 VDC

### Battery

Hot-swappable 7.4V, 5140 mAh Li-Polymer or optional 7.4V, 10280 mAh Li-Polymer

6 hours (depending on usage)

### Adapter

100 ~ 240 V, 50 ~ 60Hz / 19 VDC

## OPERATING SYSTEM

---

### Windows

Windows 10 IoT

## PHYSICAL CHARACTERISTICS With standard battery

---

### Dimensions

271.8mm (w) x 198.2mm (h) x 22mm (d)

10.7 inch (w) x 7.8 inch (h) x 0.87 inch (d)

### Weight

1.35 kg, 3 LB

## ENVIRONMENT

---

### Operating temp.

AC mode

-20°C to 60°C / -4°F to 140°F

Battery mode

-10°C to 50°C / 32°F to 122°F

### Storage temp.

-30°C to 70°C / -22°F to 158°F

### Humidity

10%-90% RH, non-condensing

### Dust and water

IP65

### Vibration

MIL-STD-810G

### Shock

MIL-STD-810G

### Drop

MIL-STD-810G (multiple 4-foot drop to concrete)