JLT1214P and JLT1214N 12" vehicle-mount computers

The preferred solution for warehousing logistics

The optimal forklift computer

The JLT1214 Series has been selected by thousands of customers in the warehousing industry around the world. The Series provides the optimal, most hassle-free solution available for forklifts and other applications in the logistics and warehousing space.

Maximized productivity and stable connectivity

Equipped with an Intel Atom[®] x6413E processor, standard 8GB DDR4 memory (expandable to 32GB), Wi-Fi 6E technology and Windows 11 support, the JLT1214 Series ensures optimal performance, stable connectivity even in busy environments, enhanced security and maximized productivity.

Docking-free solution eliminating downtime

With JLT1214 everything comes integrated in the solution, eliminating the need for external adapters or cradles. By removing unreliable cradle connections, it significantly reduces downtime. Plus, you benefit from a complete solution from a single supplier.

Overcoming common point of failure for rugged computers

The JLT1214 Series comes with the virtually unbreakable JLT PowerTouch[™] display, thereby overcoming the most common point of failure for rugged computers. It also provides a user-friendly experience even with a gloved hand and is sunlight readable.

ATIENT OF CONTRACT OF CONTRACT

KEY FEATURES

- 12" XGA LED display with the smallest footprint in its class
- Intel® x6413E processor
- IP65 waterproof and dustproof
- Virtually unbreakable JLT PowerTouch[™] display on JLT1214P
- Dual-diversity PIFA WLAN antennas
- Integrated DC/DC with UPS battery solution
- Wi-Fi 6E
- Future proof runs Windows 11 or Windows 10

HIGHLIGHTS



Consistent performance even with unstable voltage With integrated DC/DC with UPS-battery, the JLT1214 computers ensure consistent performance even with unstable voltage



Maximized uptime Complete peace of mind with JLT:Care, the no-questions-asked service agreement from JLT



Outstanding value for warehousing and logistics Smart design with everything built in makes the JLT1214 computers a cost-effective option for logistics



JLT1214P and JLT1214N 12" vehicle-mount computers

BASE UNIT

Processor Intel® x6413E

Memory 8GB DDR4 (max 32GB)

Display

JLT1214P 12.1" XGA LED 1000 NIT 12.1" XGA LED 500 NIT Capacitive touch screen with JLT PowerTouch[™] technology and hardened glass

JLT1214N 12.1" XGA LED 500 NIT Resistive 4-wire touch screen

STORAGE

SATA CFast 60GB, 120GB, 240GB

RF OPTIONS

Radio

Dualband WLAN 802.11ax, 802.11a/b/g/n/ac, MU-MIMO supported Bluetooth v5.2 4G (LTE) up to 100 Mbps download speed (optional)

GPS

A-GPS/GLONASS/BEIDOU (optional)

Antennas

WLAN dual diversity antennas (PIFA) User configurable external or internal WLAN and Bluetooth antennas

INTERFACES

Ports

4x USB 2.0 1x Ethernet 10/100/1000 1x RS232 with 5V

Speakers Waterproof stereo speakers HD audio

Buttons

Power LED dimming +/-

SECURITY

TPM module

POWER SUPPLY

Input

18-60 VDC isolated 9-36 VDC unisolated

UPS

Internal battery for graceful shut down at unexpected power outages

OPERATING SYSTEMS

Windows 11 IoT Enterprise LTSC Windows 10 IoT LTSC

PHYSICAL CHARACTERISTICS

 $\label{eq:binder} \begin{array}{l} \mbox{Dimensions} \\ \mbox{305mm (w)} \times 240\mbox{mm (h)} \times 59\mbox{mm (d)} \\ \mbox{12 inch (w)} \times 9.4 \mbox{ inch (h)} \times 2.3 \mbox{ inch (d)} \end{array}$

Weight 3.5 kg, 7.7 LB

ENVIRONMENT

Operating temp. -30° C to 55° C / -22° F to 131° F

Storage temp. -35° C to 75° C / -31° F to 167° F

Humidity 10–95% RH

Connector Sealing Roxtec sealing cable protection (optional)

Dust and water IP65 - IEC 60529:2001

Vibration 5–500 Hz/0,04 m/s2 XYZ - IEC 60068-2-64 Fh

Shock 30g for 11ms XYZ - IEC 60068-2-27

MIL-SPEC 810G in applicable areas